



MECHANICAL, MECHATRONICS & MANUFACTURING
ENGINEERING DEPARTMENT
UNIVERSITY OF ENGINEERING & TECHNOLOGY LAHORE
KSK CAMPUS

REQUEST FOR PROPOSAL (C&F BASIS)
(Re-Tender)

Sealed Tenders, on single stage, two envelope basis (TECHNICAL & FINANCIAL PROPOSAL), are invited from the Authorized Dealers and Suppliers for the supply of equipment for Mechanical, Mechatronics and Manufacturing Engineering Department of University of Engineering and Technology Lahore, Kala Shah Kaku Campus in accordance with the specifications attached with the Tender document. Earnest money 2% of total estimated approved cost i.e. Rs.800,000/- (Rs.16000/-) as per tender list shall be attached in the shape of CDR in the name of the Treasurer University of Engineering and Technology Lahore.

Detailed specifications of the equipment and other Terms & Conditions are given in the Tender Document.

The Tender Document can be obtained on the same day of publishing of Tender on PPRA Website from the Office of the Chairman of the Department of Mechanical, Mechatronics and Manufacturing Engineering, KSK Campus during the office hours (08:30 a.m. to 03:30 p.m.) on production of receipt of Rs.1000/- (Non Refundable) deposited in the University Main Account No.553-3 at Habib Bank Ltd., Engineering University Branch, Lahore or Habib Bank Ltd. UET Booth at KSK Campus. Copy of the Bidding Documents is available for information and can also be downloaded from the websites www.uet.edu.pk or www.ppra.punjab.gov.pk. In case the bidding documents are downloaded from websites, the required cost of the bidding documents shall be paid/deposited in UET Account No. 553-33 with HBL, Engineering University Branch Lahore at the time of submission of bids.

The tender will be received by hand till 24.12.2018 (10:00 a.m.) and will be opened on same date at 10:30 a.m. in the presence of available bidders/representatives in the Conference Hall adjacent to Vice Chancellor Office before Central Procurement Cell, UET, Lahore.

The firms registered under GST and of good repute are eligible to participate.

No telephonic/telegraphic/email/faxed tenders are acceptable.

Procurement shall be governed by the PPRA Punjab Rules-2014.

Dr. Zahid Anwar
Principal Investigator

UNIVERSITY OF ENGINEERING & TECHNOLOGY

KSK CAMPUS LAHORE



**TENDER DOCUMENT
(Re-Tender)**

**FOR THE PURCHASE OF EQUIPMENT
ON C&F BASE**

for

**Mechanical, Mechatronics &
Manufacturing Engineering Department
KSK Campus**

Contract Ph: 042-37951906, 042-37951907

UNIVERSITY OF ENGINEERING & TECHNOLOGY

KSK CAMPUS LAHORE


TERMS & CONDITIONS FOR RE-TENDER ON C&F BASE

1.	Single stage/two envelope bidding procedure shall be applied in response. The envelopes shall be marked as “TECHNICAL PROPOSAL” and “FINANCIAL PROPSAL”. The financial proposal of bids found technically non-responsive shall be returned unopened to the respective bidders. Technically responsive bidders shall be informed and their financial bids shall be opened in the next Central Procurement Cell (CPC) meeting after informing the technically responsive bidders.
2.	Tender must be accompanied by 2% of total estimated approved cost i.e. Rs.800,000/- of equipment (Rs.16000/-) in the shape of Deposit-at-call in the name of Treasurer, University of Engineering and Technology, Lahore without which tender will not be entertained. No Guarantee by Bank or any other organization will be accepted. However, Earnest Money of the successful bidder, will be released on receipt of the Shipping documents in the Treasurer's Office.
3.	The successful bidder will have to deposit 10% as refundable security in shape of CDR/Bank Draft of the total offer on acceptance of the tender which will be refunded/returned to the bidder after successful completion of the warranty period i.e. one year after installation/commissioning of the equipment without any interest & will arrange (3) Stamp Papers @Rs.0.25% Total Value of cost issuance of supply order/contract.
4.	The equipment quoted must be from indicated country of origin, having English operational as well as instructional manuals.
5.	The prices should be quoted in foreign currency on C&F base Lahore (by Air). Exchange rates will be considered as on the date of opening of tenders.
6.	The prices must be quoted item wise on Price schedule (Performa Annexure-A must be filled by the company).
7.	Bidders are advised not to quote different options (only one option is to be quoted). Received bid with different options shall not be entertained.
8.	Bidders should clearly indicate packing, handling, forwarding, documents charges, air freight etc. (Attached with Financial proposal)
9.	Offer should be valid for 90 days from the date of opening of tender.
10.	Letter of credit & insurance will be arranged by the University.
11.	Custom Duties and other taxes, if any, levied by the Govt. of Pakistan shall be paid by the University and should not be included in the quoted prices.
12.	The Transportation within Pakistan will be arranged and paid by the University.

13.	Delivery period will be three months (90 days) from the date of establishment of Letter of Credit, Suppliers may however, quote their best delivery period.
14.	Bidders must submit Proforma Invoice in original from their principals duly signed and clearly indicating the complete specifications of each item as pre-tender inquiry, the name of the manufacturer and country of origin along-with a certificate (as under) authorizing them to quote on their behalf. (Attached Both Proposal) <i>"This is to certify that M/s_____ have obtained quotation from us against invitation to tender due on_____ and we have agreed to supply/manufacture the stores strictly in accordance with the specifications laid down in the said invitation to tender".</i> (Attached with Technical Proposal)
15.	If the acceptance of tender issued during the validity period of the tender is not accepted by the bidder. The Earnest Money shall be forfeited and the stores purchased at his risk and expense.
16.	Any overwriting/crossing, etc. appearing in the offer may be properly signed by the person signing the tender. All pages of the tender must be properly signed & stamped. Offer with any overwriting/use of Blanco shall not be accepted in any circumstances.
17.	In case, the bidder fails to execute the contract strictly in accordance with the terms and conditions laid down in the contract, the security deposited by him shall be forfeited and the stores purchased at his risk and expense.
18.	The stores must be brand new and complete in all respects with original packing of manufacturer and strictly conforming with the given specifications.
19.	Bidders must attach attested Photocopies of their N.T.R. & E.P.B Registration with the tender. (Attached with Technical proposal)
20.	The University will get the equipment inspected at KSK Campus through an authorized Surveyor and accept or reject the equipment, if not found according to the given specifications.
21.	The University reserves the right to claim compensation for the losses caused by delay in the delivery of stores. Bank charges on account of amendment or extension in L.C. on the request of the Supplier will also be borne by the Supplier.
22.	Any conditional, ambiguous, incomplete, supplementary or revised offer after the opening of tender, shall not be entertained.
23.	Bidders should clearly indicate the name and full address of their principals in whose favour L.C. shall be opened.
24.	Bidders must have office and workshop facilities in Pakistan.
25.	Any overwriting / crossing etc. appearing in the offer, may be properly signed by the person signing the tender. All pages of the tender must be properly signed.
26.	After Sale service and supply of spare parts must be guaranteed for a period of one year. (Attached with Technical proposal)

27.	Tender received through fax / courier and e-mail shall not be acceptable.
28.	In case any material is found being not in conformity with the specifications provided in the tender either on account of inferior quality defective workmanship, faulty design, faulty packing or is short supplied or wrongly supplied, the supplier will replace such material or pay the full cost of replacement.
29.	The University will award the contract to the successful tenderer whose tender has been determined to be substantially responsive and has been determined as the lowest evaluated tender item wise.
30.	The university reserves the right at the time of award of contract to increase or decrease the quantity of equipment.
31.	Within a week of receipt of contract, the successful bidder shall sign the contract and return it to the University.
32.	The following shipping documents in quadruplicate, with number and date of the contract would be dispatched to the university by courier immediately after the shipment of the goods.
33.	Non negotiable clean Air way bill / Bill of Loading showing actual freight paid.
34.	Supplier signed invoice showing separately value of each item dully signed in ink.
35.	Signed Packing List showing measurement quantity and weight of packing & their numbers.
36.	Freight Memo
37.	Guarantee Certificate
38.	The shipment against the contract must not take place on Indian or pro-Indian ship (Like Israel, etc) or those ships which come to Pakistan after touching Israeli/Indian Ports).
39.	Bidder shall be bound to provide installation/commissioning Free of Cost on site (UET KSK Campus).
40.	Tenders shall be received by hand uptil 24 th December (Monday), 2018 till 10:00 A.M.
41.	Tenders shall be opened on 24 th December (Monday), 2018 at 10:30 A.M. in the presence of available bidders/representatives in the Conference Hall adjacent to Vice Chancellor Office before Central Procurement Cell, UET, Lahore.
42.	Country of Origin, Model, and date of manufacturing / assembly of all equipment shall be mentioned. (Attached with Technical proposal)
43.	Sale price of the tender document is Rs.1000/- (Non-Refundable) . The details specifications of the required equipment are given in the subsequent pages.
44.	The prices must be quoted item wise.
45.	The bidders are required to submit the company profile including Technical, Engineering, managerial capabilities after-sale service and past experience / performance along-with their Technical bid and also list of reference installation in Pakistan for similar equipments. (Attached with proposal)

46.	The bidders will arrange full training of equipment to University Staff for successful running functioning of the equipment free of cost.
47.	Procurements shall be governed by the PPRA Punjab Rules-2014.


Dr. Zahid Anwar
Principal Investigator

Detailed Specifications of the Tendered Equipment

Sr. No.	Item Name & Specifications	Quantity	Country of Origin	Estimated Price (Rs.)																																																																												
1.	<p>Thermal Conductivity Analyzer</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center;">OPERATING ENVIRONMENT</th> </tr> </thead> <tbody> <tr> <td colspan="2">Controller</td> </tr> <tr> <td>Range</td> <td>0-50 °C</td> </tr> <tr> <td>Power</td> <td>5 AA batteries</td> </tr> <tr> <td>Read Modes</td> <td>Manual and unattended measurement</td> </tr> <tr> <td colspan="2">Sensors</td> </tr> <tr> <td>Range</td> <td>-50 to 150 °C</td> </tr> <tr> <th colspan="2" style="text-align: center;">PHYSICAL CHARACTERISTICS</th> </tr> <tr> <td colspan="2">Controller</td> </tr> <tr> <td>Length</td> <td>18.5 cm</td> </tr> <tr> <td>Width</td> <td>10 cm</td> </tr> <tr> <td>Height</td> <td>3.5 cm</td> </tr> <tr> <td colspan="2">Display size</td> </tr> <tr> <td>Width</td> <td>5.5 cm</td> </tr> <tr> <td>Height</td> <td>4.0 cm</td> </tr> <tr> <td colspan="2">Sensor interface</td> </tr> <tr> <td>Sensor interface</td> <td>DB-15 connector</td> </tr> <tr> <th colspan="2" style="text-align: center;">SENSORS</th> </tr> <tr> <td colspan="2">KS-3 (6-cm [small] single needle)</td> </tr> <tr> <td>Conductivity Range</td> <td>0.02-2.00 W/(m • K)</td> </tr> <tr> <td>Resistivity Range</td> <td>50-5,000 °C • cm/W</td> </tr> <tr> <td>AccuracyConductivity</td> <td>±10% from 0.2-2.0 W/(m • K)</td> </tr> <tr> <td>Size</td> <td>1.3 mm diameter × 60 mm length</td> </tr> <tr> <td colspan="2">TR-3 (10-cm [large] single needle)</td> </tr> <tr> <td>Conductivity Range</td> <td>0.1-4.0 W/(m • K)</td> </tr> <tr> <td>Resistivity Range</td> <td>25-1,000 °C • cm/W</td> </tr> <tr> <td>Accuracy Conductivity</td> <td>±10% from 0.1-4.0 W/(m • K)</td> </tr> <tr> <td>Size</td> <td>2.4 mm diameter × 100 mm length</td> </tr> <tr> <td colspan="2">SH-3 (3-cm dual-needle)</td> </tr> <tr> <td>Conductivity Range</td> <td>0.02-2.00 W/(m • K)</td> </tr> <tr> <td>Resistivity Range</td> <td>0.02-2.00 W/(m • K)</td> </tr> <tr> <td>Diffusivity Range</td> <td>0.1-1.0 mm²/s</td> </tr> <tr> <td>Volumetric specific heat capacity Range</td> <td>0.5-4.0 MJ/m³</td> </tr> <tr> <td>AccuracyConductivity</td> <td>±10% from 0.02-2.0 W/(m • K)</td> </tr> <tr> <td>AccuracyDiffusivity</td> <td>±10% at conductivity above 0.2 W/(mK)</td> </tr> <tr> <td>Diffusivity Accuracy</td> <td>±0.02 W/(m • K) from 0.10-0.20 W/(mK)</td> </tr> <tr> <td>Volumetric specificheat capacityAccuracy</td> <td>±10% at conductivities above 0.1 W/(mK)</td> </tr> <tr> <td>Size</td> <td>1.3mm diameter×30mm length,6mm spacing</td> </tr> </tbody> </table>	OPERATING ENVIRONMENT		Controller		Range	0-50 °C	Power	5 AA batteries	Read Modes	Manual and unattended measurement	Sensors		Range	-50 to 150 °C	PHYSICAL CHARACTERISTICS		Controller		Length	18.5 cm	Width	10 cm	Height	3.5 cm	Display size		Width	5.5 cm	Height	4.0 cm	Sensor interface		Sensor interface	DB-15 connector	SENSORS		KS-3 (6-cm [small] single needle)		Conductivity Range	0.02-2.00 W/(m • K)	Resistivity Range	50-5,000 °C • cm/W	AccuracyConductivity	±10% from 0.2-2.0 W/(m • K)	Size	1.3 mm diameter × 60 mm length	TR-3 (10-cm [large] single needle)		Conductivity Range	0.1-4.0 W/(m • K)	Resistivity Range	25-1,000 °C • cm/W	Accuracy Conductivity	±10% from 0.1-4.0 W/(m • K)	Size	2.4 mm diameter × 100 mm length	SH-3 (3-cm dual-needle)		Conductivity Range	0.02-2.00 W/(m • K)	Resistivity Range	0.02-2.00 W/(m • K)	Diffusivity Range	0.1-1.0 mm ² /s	Volumetric specific heat capacity Range	0.5-4.0 MJ/m ³	AccuracyConductivity	±10% from 0.02-2.0 W/(m • K)	AccuracyDiffusivity	±10% at conductivity above 0.2 W/(mK)	Diffusivity Accuracy	±0.02 W/(m • K) from 0.10-0.20 W/(mK)	Volumetric specificheat capacityAccuracy	±10% at conductivities above 0.1 W/(mK)	Size	1.3mm diameter×30mm length,6mm spacing	01	USA	800,000/-
OPERATING ENVIRONMENT																																																																																
Controller																																																																																
Range	0-50 °C																																																																															
Power	5 AA batteries																																																																															
Read Modes	Manual and unattended measurement																																																																															
Sensors																																																																																
Range	-50 to 150 °C																																																																															
PHYSICAL CHARACTERISTICS																																																																																
Controller																																																																																
Length	18.5 cm																																																																															
Width	10 cm																																																																															
Height	3.5 cm																																																																															
Display size																																																																																
Width	5.5 cm																																																																															
Height	4.0 cm																																																																															
Sensor interface																																																																																
Sensor interface	DB-15 connector																																																																															
SENSORS																																																																																
KS-3 (6-cm [small] single needle)																																																																																
Conductivity Range	0.02-2.00 W/(m • K)																																																																															
Resistivity Range	50-5,000 °C • cm/W																																																																															
AccuracyConductivity	±10% from 0.2-2.0 W/(m • K)																																																																															
Size	1.3 mm diameter × 60 mm length																																																																															
TR-3 (10-cm [large] single needle)																																																																																
Conductivity Range	0.1-4.0 W/(m • K)																																																																															
Resistivity Range	25-1,000 °C • cm/W																																																																															
Accuracy Conductivity	±10% from 0.1-4.0 W/(m • K)																																																																															
Size	2.4 mm diameter × 100 mm length																																																																															
SH-3 (3-cm dual-needle)																																																																																
Conductivity Range	0.02-2.00 W/(m • K)																																																																															
Resistivity Range	0.02-2.00 W/(m • K)																																																																															
Diffusivity Range	0.1-1.0 mm ² /s																																																																															
Volumetric specific heat capacity Range	0.5-4.0 MJ/m ³																																																																															
AccuracyConductivity	±10% from 0.02-2.0 W/(m • K)																																																																															
AccuracyDiffusivity	±10% at conductivity above 0.2 W/(mK)																																																																															
Diffusivity Accuracy	±0.02 W/(m • K) from 0.10-0.20 W/(mK)																																																																															
Volumetric specificheat capacityAccuracy	±10% at conductivities above 0.1 W/(mK)																																																																															
Size	1.3mm diameter×30mm length,6mm spacing																																																																															

PRICE SCHEDULE OF SCIENTIFIC INSTRUMENTS TO BE IMPORTED FOR _____
 (MECHANICAL, MECHATRONICS AND MANUFACTURING ENGINEERING DEPARTMENT, KSK CAMPUS)

Item No.	Description	Country of Origin	Name of Foreigner Supplier	Unit Price	Total Price	By Air LHR	Remarks
1.							
2.							
3.							
4.							
5.							
6.							
7.							
8.							
9.							
10.							
11.							
12.							
13.							
14.							

Signature duly stamp
Of Supplier